

TECHNICAL DOCUMENTATION O-RINGS - JIS Sizes V Series

Size	ID			C/S (W)			±
	mm	±	mm	in	±	in	
V-15	14.5	0.15	4.0	0.571	0.006	0.157	0.004
V-24	23.5	0.15	4.0	0.925	0.006	0.157	0.004
V-34	33.5	0.15	4.0	1.319	0.006	0.157	0.004
V-40	39.5	0.15	4.0	1.555	0.006	0.157	0.004
V-55	54.5	0.25	4.0	2.146	0.010	0.157	0.004
V-70	69.0	0.25	4.0	2.717	0.010	0.157	0.004
V-85	84.0	0.40	4.0	3.307	0.016	0.157	0.004
V-100	99.0	0.40	4.0	3.898	0.016	0.157	0.004
V-120	119.0	0.40	4.0	4.685	0.016	0.157	0.004
V-150	148.5	0.60	4.0	5.846	0.024	0.157	0.004
V-175	173.0	0.60	4.0	6.811	0.024	0.157	0.004
V-225	222.5	0.80	6.0	8.760	0.031	0.236	0.006
V-275	272.0	0.80	6.0	10.709	0.031	0.236	0.006
V-325	321.5	1.00	6.0	12.657	0.039	0.236	0.006
V-380	376.0	1.00	6.0	14.803	0.039	0.236	0.006
V-430	425.5	1.20	6.0	16.752	0.047	0.236	0.006
V-480	475.0	1.20	10.0	18.701	0.047	0.394	0.012
V-530	524.5	1.60	10.0	20.650	0.063	0.394	0.012
V-585	579.0	1.60	10.0	22.795	0.063	0.394	0.012
V-640	633.5	1.60	10.0	24.941	0.063	0.394	0.012
V-690	683.0	1.60	10.0	26.890	0.063	0.394	0.012
V-740	732.5	2.00	10.0	28.839	0.079	0.394	0.012
V-790	782.0	2.00	10.0	30.787	0.079	0.394	0.012
V-845	836.5	2.00	10.0	32.933	0.079	0.394	0.012
V-950	940.5	2.50	10.0	37.028	0.098	0.394	0.012
V-1055	1044.0	3.00	10.0	41.102	0.118	0.394	0.012